

Silverwax 305

SECTION 1. IDENTIFICATION

Product Identifier	Silverwax 305
Other Means of Identification	BRAKE AND PARTS CLEANER
Product Family	Cleaner
Recommended Use	Cleans asbestos dust, oil, grease and brake liquid.
Manufacturer	Laboratoire Hygienex Inc. 6400 Zéphirin-Paquet Québec, Québec, G2C-0M3 (418) 522-2332 www.hygienex.com
Emergency Phone No.	CANUTEC, (613) 996-6666
SDS No.	305

SECTION 2. HAZARD IDENTIFICATION

Classified according to Canada's Hazardous Products Regulations (WHMIS 2015).

Classification

Flammable liquid - Category 1; Skin irritation - Category 2; Reproductive toxicity - Category 1; Specific target organ toxicity (single exposure) - Category 3; Aspiration hazard - Category 1

Label Elements



Signal Word:

Danger

Hazard Statement(s):

H225	Highly flammable liquid and vapour.
H313 + H333	May be harmful in contact with skin or if inhaled.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.

Precautionary Statement(s):

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P241	Use explosion-proof equipment.
P243	Take precautionary measures against static discharge.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.

Response:

Product Identifier: Silverwax 305 - Ver. 1
Date of Preparation: mai 28, 2018
Date of Last Revision:

SDS No.: 305

Page 01 of 05

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers	Other Names
n-Heptane	142-82-5	80-100	Not Applicable	Not Applicable
isopropanol	67-63-0	5-10	Not Applicable	Not Applicable
Methanol	67-56-1	3-7	Not Applicable	Not Applicable

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Move to fresh air. Keep at rest in a position comfortable for breathing. Call a Poison Centre or doctor if you feel unwell.

Skin Contact

Take off immediately contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Get medical advice or attention if you feel unwell or are concerned.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice or attention.

Ingestion

Rinse mouth with water. Get medical advice or attention if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam.

Specific Hazards Arising from the Product

Highly flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air.

Special Protective Equipment and Precautions for Fire-fighters

Evacuate area. For a massive fire, immediately evacuate the area and use unmanned hose holder or monitor nozzles.

Fight fire from a protected, explosion-resistant location or maximum distance possible.

Fire-fighters should enter area wearing specialized protective equipment. (Bunker Gear will not provide adequate protection.).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet. Increase ventilation to area or move leaking container to a well-ventilated and secure area.

Product Identifier: Silverwax 305 - Ver. 1

SDS No.: 305

Date of Preparation: mai 28, 2018

Date of Last Revision:

Page 02 of 05

Environmental Precautions

It is good practice to prevent releases into the environment.

Methods and Materials for Containment and Cleaning Up

Review Section 7 (Handling) of this safety data sheet before proceeding with clean-up. Contain and soak up spill with absorbent that does not react with spilled product. Do NOT use combustible materials such as sawdust. Place used absorbent into suitable, covered, labelled containers for disposal. Large spills or leaks: remove or recover liquid using pumps or vacuum equipment. Dike and recover contaminated water for appropriate disposal. Collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal. Get expert advice before treating the spilled product with other chemicals to make it less hazardous. Store recovered product in suitable containers that are: contact emergency services and manufacturer/supplier for advice.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Avoid breathing in this product. Prevent skin contact. Avoid repeated or prolonged skin contact. Do not get in eyes, on skin or on clothing. Do not swallow. Only use where there is adequate ventilation. Avoid generating vapours or mists. Avoid release to the environment. Immediately report leaks, spills or failures of the safety equipment (e.g. ventilation system). Eliminate heat and ignition sources such as sparks, open flames, hot surfaces and static discharge. Post "No Smoking" signs. Do not spray on an open flame or other ignition source. Do not pierce or burn container, even after use.

Conditions for Safe Storage

Store in an area that is: cool, temperature-controlled, well-ventilated, out of direct sunlight and away from heat and ignition sources, an approved, fire-resistant area, separate from incompatible materials (see Section 10: Stability and Reactivity), clear of combustible and flammable materials (e.g. old rags, cardboard).

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Appropriate Engineering Controls

Do not allow product to accumulate in the air in work or storage areas, or in confined spaces. Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles. Wear chemical safety goggles and face shield when contact is possible.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots. Verify carefully the gloves condition before each use.

Respiratory Protection

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Clear colourless.
pH	Not applicable
Melting Point/Freezing Point	Not applicable (melting); Not applicable (freezing)
Flash Point	~ -7 °C (open cup)
Vapour Pressure	Not available
Solubility	Insoluble in water; Soluble in all proportions in common organic solvents.
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Viscosity	Not available (kinematic)
Other Information	

Product Identifier: Silverwax 305 - Ver. 1

SDS No.: 305

Date of Preparation: mai 28, 2018

Date of Last Revision:

Page 03 of 05

Physical State Liquid
Surface Tension Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

This product may produce a dangerous reaction in contact with oxidizing materials or concentrated acids.

Conditions to Avoid

Heat. High temperatures. Prolonged exposure to high temperatures. Open flames, sparks, static discharge, heat and other ignition sources.

Incompatible Materials

Oxygen, oxidizing agents (e.g. peroxides).

SECTION 11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
n-Heptane	103000 mg/m ³ (rat) (4-hour exposure)	15000 mg/kg (rat) (4-hour exposure)	2000 mg/kg (rabbit) (4-hour exposure)
isopropanol	55 mg/L (rat) (4-hour exposure)	4720 mg/kg (rat) (4-hour exposure)	12890 mg/kg (rabbit) (4-hour exposure)

Skin Corrosion/Irritation

Repeated or prolonged exposure can irritate or burn the skin.

Serious Eye Damage/Irritation

May cause serious eye damage based on information for closely related materials.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May be toxic by inhalation.

Skin Absorption

This product is absorbed by the respiratory tract and the digestive tract.

Ingestion

May be toxic by ingestion.

Aspiration Hazard

May be drawn into the lungs (aspirated) if swallowed or vomited.

Respiratory and/or Skin Sensitization

No information was located.

Reproductive Toxicity

Sexual Function and Fertility

May cause effects on sexual function and/or fertility.

Effects on or via Lactation

No information was located.

Product Identifier: Silverwax 305 - Ver. 1
Date of Preparation: mai 28, 2018
Date of Last Revision:

SDS No.: 305

Page 04 of 05

Germ Cell Mutagenicity

No information was located.

Interactive Effects

No information was located.

SECTION 12. ECOLOGICAL INFORMATION**Persistence and Degradability**

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal Methods**

Dispose of contents and container in accordance with local, regional, national and international regulations. Store product for disposal as described under Storage in Section 7 of this safety data sheet. Empty containers retain product residue. Follow label warnings even if container appears to be empty. Do not reuse empty containers.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
TMD au Canada	UN1206	LIQUIDE INFLAMMABLE (n-Heptane)	Classe 3	II

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15. REGULATORY INFORMATION**Safety, Health and Environmental Regulations**

Classified according to Canada's hazardous Regulations (WHMIS 2015).

SECTION 16. OTHER INFORMATION

Date of Preparation mai 28, 2018

Key to Abbreviations CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

References <https://echa.europa.eu/fr/>
<http://www.csst.qc.ca/Pages/index.aspx>.
Security data sheets of the suppliers.

Additional Information The preceding indications are based on our current knowledge but do not represent a guaranty in terms of the product's proprieties and do not establish a legally valid contractual relationship. The manipulation and use conditions of the product go beyond the rep's control. It is the user's responsibility to evaluate all available information before using the product, no matter the type of use, and to respect all local, provincial and federal legislations and laws.

Product Identifier: Silverwax 305 - Ver. 1

SDS No.: 305

Date of Preparation: mai 28, 2018

Date of Last Revision:

Page 05 of 05